



ÖN IT.

CREATING RESULTS.



PRODUCT GUIDE

WHY SCHÖNOX?

Schönox provides solutions to subfloor challenges with primers and moisture mitigation systems, repair, patching and smoothing products, floor-leveling compounds, adhesives, and waterproofing materials.

Schönox was founded more than 125 years ago in Germany and is active in more than 40 countries worldwide. In North America, HPS Schönox is marketing and distributing products geared toward the specific needs of the marketplace. We provide technical support and education throughout the nation, including training locations in Las Vegas, Nev., and Florence, Ala. We continue to grow based on the strength of our products and the way we do business.



RENOVATION WITHOUT DEMOLITION

The last thing that you want to do with a flooring project is go backwards with the demolition of the subfloor. Often, we can avoid those demolition efforts with a series of products to support critical substrates allowing you to save time and money.

Schönox leveling compounds allow most subfloors to be renovated rather than demolished, resulting in a more economical and environmentally responsible project solution. Rough, uneven floors. Deteriorating ordinary gypsum. Residual carpet glue. Asbestos cutback. Unsound wood subfloors. We have product solutions for all of these issues and more.

BETTER FLOORS, BETTER ENVIRONMENT

Our products are really green. You hear it all the time. But what does it mean? Delve into our products. You'll find floor-leveling compounds made from the by-product of fossil fuel power plant emissions, primers and adhesives with no VOCs, and a product series that dramatically cuts subfloor demolition material going to landfills.

DUST-REDUCED TECHNOLOGY



When has dust ever not been an issue on a job site? Schönox has the answer. Special properties in our Schönox AP, APF, AP Rapid, AP Rapid Plus, AST, RF, and ZM dramatically reduce the amount of dust created when mixing and using them.

IMO CERTIFIED PRODUCTS



Schönox International Maritime Organization approved products have undergone extensive testing in accordance with relevant approval procedures and were found in compliance with the requirements of international standards and are accepted by the United States Coast Guard (USCG).

LEED CREDITS

The synthetic gypsum used in our Schönox AP, APF, AP Rapid, AP Rapid Plus, and AST products is verified as: Low-Emitting Material, Building Reuse, Construction Waste Management, Materials Reuse, Recycled Content. As such, the use of these products has the added benefit of contributing toward LEED credits. In fact, all of our products contribute to LEED credits. To learn more, visit hpsubfloors.com

VOCs

Whether you are priming, leveling, repairing, or installing, we have products that meet the most stringent VOC requirements in America and Europe. Breathe easy on your next project and feel confident that those around you can do the same with Schönox subfloor products **ÖN IT**.

WE ARE ÖN IT.

We believe that anything less than a perfect floor is failure. So when you need the most technically advanced subfloor systems in the industry, Schönox is **ÖN IT**. When you have questions about how to level a floor from hell, our team is **ÖN IT**. When you're up against an insane deadline, count on us to be **ÖN IT**. Wherever you seek innovation, reliability, and lasting results, we're **ÖN IT**. You deserve a partner that's here to help you take all of your projects to a whole new level. That's why for everything you put into your job, you want **Schönox ÖN IT**.

**HPS Schönox headquartered in Florence, Alabama.
HPS Schönox West located in Las Vegas, Nevada.**



We are in the field every day working with the people who make flooring projects happen.



OUR PRODUCT CATEGORIES

PRIMERS

KH FIX | VD | SHP

MOISTURE MITIGATION SYSTEMS

SDG PLUS | MR 18 | EPA | EPA RAPID

REPAIR, PATCHING & SMOOTHING COMPOUNDS

SL | AST | HS STURDY | RF | PL
SEZ PLUS | SGH

FLOOR-LEVELING COMPOUNDS

S1500 | US | XM | ZM | ZM RAPID
DSP | DSP PLUS | AP | APF
AP RAPID | AP RAPID PLUS

UNDERLAYMENTS

TS | RENOTEX® | RENOTEX® 3D
SOUND INSULATION SHEET

ADHESIVES

ROLL AND GO™ | EMICLASSIC | MULTIFIX
HPS 1100 | HPS 92 | PU 900 | PROTECT

WATERPROOFING & CRACK ISOLATION MATERIALS

HA | iFIX™

WATERPROOFING ACCESSORIES

AB-SEALING AND UNCOUPLING MEMBRANE
ST-SEALING TAPE
IC-INTERIOR CORNERS
EA-EXTERIOR CORNERS
ST FC-SLEEVE
ST D 8-PIPE COVER
ST D 15-PIPE COVER

TOOLS & ACCESSORIES

Stay **ÖN IT!** You can find comprehensive information on all of our products and more by going to **hpsubfloors.com** or by downloading the **Schönox app** for free on the **App Store** or **Google Play**.



PRIMERS & MOISTURE MITIGATION SYSTEMS

For comprehensive information on all of our Primers & Moisture Mitigation Systems go to hpsubfloors.com.



SCHÖNOX KH Fix FOR POROUS SUBSTRATES Ready-Mixed, Solvent-Free Acrylic Primer

Especially suitable on existing gypsum substrates to bind residual dust, reduce absorbency, and improve adhesion. **Interior and exterior use.**

Unit Size: 2.5 gal/unit



SCHÖNOX VD FOR POROUS SUBSTRATES Dilutable Acrylic Primer

Especially suitable for use prior to applying Schönox underlayments on porous substrates. Suitable for priming on walls and floors following the recommended dilution rates. **Interior and exterior use.**

Unit Size: 2.5 gal/unit



SCHÖNOX SHP FOR NON-POROUS SUBSTRATES Ready-Mixed Acrylic Primer

For use on sound, smooth, and non-porous substrates, especially before use of Schönox underlayments on ceramic tiles, old vinyl, linoleum, plywood, OSB, and rubber coverings. **Interior and exterior use.**

Unit Size: 1 gal/unit and 2.5 gal/unit

SCHÖNOX SDG PLUS

Rapid-Drying, Ready-Mixed
Acrylic Moisture Mitigation
System and Primer



Suitable on cement-based substrates, residual moisture up to 96% RH or 18 lbs./1000 sq. ft./24 hrs. in **interior areas** before applying Schönox underlayments. One coat, back roll.

Unit Size: 3 gal/unit

SCHÖNOX MR 18

One-Component, Rapid-Drying,
Polyurethane, Ready-Mixed
Moisture Mitigation System and
Substrate Solidifier



A fast-curing system suitable on **interior**, cement-based substrates up to 96% RH or 18 lbs./1,000 sq. ft./24hrs. before applying Schönox underlayments. Recommended as a solidifier over a variety of critical substrates, such as adhesive residues and gypsum substrates.

Unit Size: 2.5 gal/unit

SCHÖNOX EPA

READY FOR LEVELING IN 4-6 HOURS*

Two-Part, Rapid-Drying,
Epoxy-Based Moisture Mitigation
System and Migration Barrier



Suitable on porous, concrete slabs with residual moisture up to 100% RH or 25 lbs./1000 sq. ft./24 hrs. in **interior or exterior areas** before applying Schönox underlayments.

Unit Size: Part A (resin): 1.47 gal.
Part B (hardener): 0.96 gal.

Coverage: Approx. 290 sq. ft.

SCHÖNOX EPA RAPID

READY FOR LEVELING IN 2-3 HOURS*

Two-Part, Rapid-Drying,
Epoxy-Based Moisture Mitigation Sys-
tem and Migration Barrier



Suitable on porous, concrete slabs with residual moisture up to 100% RH or 25 lbs./1000 sq. ft./24 hrs. in **interior or exterior areas** before applying Schönox underlayments.

Unit Size: Part A (resin): 1.68 gal.
Part B (hardener): 0.77 gal.

Coverage: Approx. 300 sq. ft.

*Refer to Technical Data Sheets for more information.

Toll Free: 855.391.2649 5



REPAIR, PATCHING & SMOOTHING PRODUCTS

For comprehensive information on all of our Repair, Patching & Smoothing Products by go to hpsubfloors.com.



SCHÖNOX SL

MOISTURE-RESISTANT

Cement-Based, Rapid-Drying, Smoothing and Finishing Compound

Provides a smooth finish on a variety of substrates in **interior areas**. A true high-performance featheredge up to 1". No priming required, unless over gypsum.

Unit Size: 10lb. net wt.

PSI: 3700



SCHÖNOX AST

DUST-REDUCED

Synthetic Gypsum-Based, Rapid-Drying, Smoothing and Patching Compound

Provides a smooth finish on various substrates in **interior areas**. Can be installed as a true featheredge up to 1/4". Excellent for light repair over gypsum substrates.

Unit Size: 10lb. and 33lb. net wt.

PSI: 3600



NEW SCHÖNOX HS STURDY

HYBRID ACTIVE-DRY TECHNOLOGY

DUST-REDUCED

Rapid-Drying Repair and Smoothing Compound

Provides a smooth finish on a variety of substrates in **interior areas**. Can be installed as a true featheredge up to 2". Patented technology provides versatility and strength.

Unit Size: 33lb. net wt.

PSI: 4400



SCHÖNOX RF

DUST-REDUCED

Cement-Based, Rapid-Setting, Smoothing and Patching Compound

Excellent for ramping, filling cracks and holes, or for repairing concrete stairs.

For interior use. Can be installed up to 2", finer aggregates.

Unit Size: 33lb. net wt.

PSI: 4200



SCHÖNOX PL

MOISTURE-RESISTANT - EXTERIOR

Cement-Based, Universal Repair Mortar

Suitable on all cement and gypsum-based substrates. Designed for rapid-drying patches and repairs in **interior and exterior** areas. Schönox PL can be installed up to 2"

Unit Size: 55lb. net wt.

PSI: 4200



SCHÖNOX SEZ PLUS

TRENCH FILLER UP TO 10"

Rapid-Setting Sand Cement Screed

Non-sagging cement screed for filling trenches or concrete voids. Perfect for use as aggregate with all Schönox cementitious self-levelers. Ready for covering after approximately 24 hours and up to 72 hours. **For interior use only.**

Unit Size: 55lb. net wt.

PSI: 6500



SCHÖNOX SGH

READY TO COVER AFTER 1 HR*

Rapid-Curing, Two-Part, Non-Shrinking, Crack Repair Compound

Suitable for filling dormant concrete and screed cracks, saw cuts or dummy joints, and for bonding nail battens, metal profiles as well as natural and artificial stones on porous and non-porous substrates. Loadable after 15-45 min. Renovation clips included.

Unit Size: Part A: 300 ml, Part B: 300 ml

*Refer to Technical Data Sheets for more information.

Toll Free: 855.391.2649 7



FLOOR-LEVELING COMPOUNDS, TOPPINGS & UNDERLAYMENTS

Pumpable and suitable on all cement and gypsum substrates. For more information go to hpsubfloors.com.



SCHÖNOX S1500

**Cement-Based,
Self-Leveling Compound***

Suitable on all cement and gypsum substrates. May be installed in depth ranging from 1/8" to 1 1/2" with minimal shrinkage. **For interior use only.** Up to 40 min. pot life. Ready for covering after approximately 4-24 hours.

Unit Size: 55lb. net wt.

PSI: 2400 after 1 day

PSI: 4900 after 28 days

*Available in select regions



SCHÖNOX US

WATER- & FROST-RESISTANT

**Cement-Based,
Self-Leveling Compound**

Suitable on cement and gypsum-based substrates. Can be installed from 1/8" up to 3". Up to 40 min. pot life. Ready for covering after approximately 4-24 hours at 1/4". Designed for fast leveling in **interior and exterior areas**. Great for use as a shower pan.

Unit Size: 55lb. net wt.

PSI: 2000 after 1 day

PSI: 4250 after 28 days



SCHÖNOX XM

Cement-Based, Self-Leveling and Smoothing Compound

Characterized by good working properties, standard preparation and cost-effective applications in **interior areas**. Suitable for layers up to 1/2". Up to 30 min. pot life. Ready for covering after approximately 3-24 hours.

Unit Size: 55lb. net wt.

PSI: 2000 after 1 day

PSI: 4300 after 28 days



SCHÖNOX ZM

**MOISTURE-RESISTANT
DUST-REDUCED**

**Cement-Based,
Self-Leveling Compound**

Designed for fast leveling of floors in **interior areas**. Can be installed up to 1". Ready for covering after approximately 2-16 hours at 1/4".

Unit Size: 55lb. net wt.

PSI: 2400 after 1 day

PSI: 5800 after 28 days



SCHÖNOX ZM RAPID

90 MINUTE RAPID-SETTING

Self-Leveling Compound

Designed for fast-track leveling of floors in **interior areas**. Many types of floor coverings can be installed after 1.5 to 2 hours.

Can be installed up to 1".

Unit Size: 55lb. net wt.

PSI: 5000 after 1 day

PSI: 7550 after 28 days

*Refer to Technical Data Sheets for more information.



FLOOR-LEVELING COMPOUNDS, TOPPINGS & UNDERLAYMENTS

Pumpable and suitable on all cement and gypsum substrates. For more information go to hpsubfloors.com.



SCHÖNOX DSP

WATER- & FROST-RESISTANT

**Wear-Rated, Cement-Based
Self-Leveling Concrete Topping**

Designed for a variety of applications over suitable substrates in residential, commercial, and industrial areas. Provides an extremely dense and durable surface to be polished in **interior and exterior areas**. Can be installed above 1/4" up to 2".

Unit Size: 55lb. net wt.

PSI: 2000 after 1 day

PSI: 7250 after 28 days



SCHÖNOX DSP PLUS

WATER- & FROST-RESISTANT

**Wear-Rated, Polishable, Cement-Based,
Self-Leveling Concrete Topping**

Suitable for same applications as Schönox DSP but **with larger aggregate**. Provides an extremely dense and durable surface to be polished in **interior and exterior areas**. Can be installed at a minimum of 3/8" up to 2". Additional aggregate or pigment may be added.

Unit Size: 55lb. net wt.

PSI: 4250 after 1 day

PSI: 7250 after 28 days

SYNTHETIC FLOOR-LEVELING SYSTEMS

Our Schönox AP, APF and AST are synthetic gypsum products manufactured from the purified emissions taken from the smoke stacks of fossil-fueled power plants. Once fortified using a special conversion method, the final synthetic gypsum is far superior to ordinary gypsum. These products can go over many critical substrates, dry to an outstanding 5800 to 6200 PSI, and do not shrink. And as with all Schönox products, AP, APF, and AST contain no fly ash.

MORE ABOUT SYNTHETIC GYPSUM

Synthetic gypsum is man-made from recycled by-products, where calcium sulfate is reclaimed, while natural gypsum is mined from the earth. These are chemically identical, yet offer very different performance characteristics. Synthetic gypsum contains no organic material and does not support mold growth, while natural gypsum contains organic matter that does support mold growth. The fortification and drying process of synthetic gypsum produces alpha-hemihydrate for superior hardness and strength while the drying process for natural gypsum produces beta-hemihydrate with inferior hardness and strength.

SCHÖNOX AP

DUST-REDUCED

Synthetic Gypsum,
Self-Leveling Compound

Especially suited on cement, gypsum, and various critical substrates. Designed for refurbishment work in **interior areas**. Can be installed up to 2" with no shrinkage.

Unit Size: 55lb. net wt.

PSI: 2100 after 1 day

PSI: 5800 after 28 days



SCHÖNOX APF

DUST-REDUCED

Synthetic Gypsum, Fiber-Reinforced
Self-Leveling Compound

Especially suited for wooden floors as well as other critical substrates, and on sound low pile carpet. Designed for refurbishment work in **interior areas**. Embedded fibers provide a reinforcement making it unnecessary to lay a reinforcement fabric. Can be installed above 1/8" up to 1" with no shrinkage.

Unit Size: 55lb. net wt.

PSI: 2400 after 1 day

PSI: 6200 after 28 days



*Refer to Technical Data Sheets for more information.

Toll Free: 855.391.2649 11

HYBRID ACTIVE-DRY TECHNOLOGY



The next generation of synthetics are hybrid leveling compounds. Schönox AP Rapid and AP Rapid Plus 100% active-drying, rapid-curing self-levelers offer the benefits of both worlds by combining the versatility, strength, and durability of synthetic gypsum with the speed of fast-curing cement. AP Rapid and AP Rapid Plus, specifically designed for high-humidity environments, dry independent of temperature and humidity, are pumpable and true self-leveling with very low shrinkage. Dust-reduced properties, low VOC content, and possible LEED credit contribution only add to the many advantages of Schönox's hybrid leveling compounds. Ask us about sound ratings.



SCHÖNOX AP RAPID

HYBRID ACTIVE-DRY TECHNOLOGY DUST-REDUCED

Pumpable Self-Leveling Compound

Designed for fast-track installations on most substrates in **interior areas**. May be installed above 1/16" up to 1/2". Suitable on concrete, cement, gypsum, old flooring, old water-resistant residues, OSB, and plywood and leveling of substrates under flexible coverings and wood flooring. Ready for covering after 6 hours at 1/4".

Unit Size: 55lb. net wt.

PSI: 3800 after 1 day

PSI: 5800 after 28 days



SCHÖNOX AP RAPID PLUS

HYBRID ACTIVE-DRY TECHNOLOGY DUST-REDUCED

Pumpable Self-Leveling Compound

Designed for deep pour, fast track installations on most substrates in **interior areas**. May be installed above 1/8" up to 3". Suitable on concrete, cement, gypsum, old flooring, old water-resistant residues, OSB, and plywood and leveling of substrates under flexible coverings and wood flooring. Ready for covering after 16 hours at 1/2" and 48 hours at 2-3".

Unit Size: 55lb. net wt.

PSI: 3800 after 1 day

PSI: 6300 after 28 days




SCHÖNOX TS

Impact Sound Insulation Underlayment

Suitable for improving impact sound insulation, heat insulation, and living comfort in residential areas.

Total sq.ft.: 215.2 sq.ft./roll
Roll Size: 65.61 ft. L, 3.28 ft. W
Acoustic Sound Improvement:
Approx. **17dB**
Impact Sound Improvement:
Approx. **20dB**




SCHÖNOX RENOTEX®

Multiaxial Glass Fiber Fabric

Developed to be used with Schönox APF to reinforce critical substrates in renovation projects. May also be used for other installations where additional reinforcement is needed.

Total sq.ft.: 542.5 sq.ft./roll
Roll Size: 137.8 ft. L, 3.94 ft. W



SCHÖNOX RENOTEX® 3D

UL CLASSIFIED AS PART OF THE RENOTEX 3D SYSTEM*

Multi-Dimensional Glass Fiber Reinforcement Fabric

Combine with Schönox AP Rapid Plus and suitable sound insulation layer over wooden substrates to create a floating construction.

Total sq.ft.: approx. 538 sq.ft./roll
Roll Size: 82 ft. L, 6.5 ft. W



SOUND INSULATION SHEET

UL CLASSIFIED AS PART OF THE RENOTEX 3D SYSTEM*

Light, Flexible, Mineral Wool Layer

Combine with Schönox AP Rapid Plus and Schönox Renotex® 3D to create UL Classified floating construction over wooden substrates. Improves sound transmission, impact sound and thermal insulation.

Sheet Size: 4 ft. L, 2 ft. W
Total sq.ft.: 96 sq.ft./pack

*Refer to Technical Data Sheets for more information.

Toll Free: 855.391.2649 13



ADHESIVES

For comprehensive information on all of our Adhesives go to hpsubfloors.com.



SCHÖNOX ROLL and GO™ PH IRRELEVANT UP TO 85% RH

**Rollable Acrylic Adhesive for
Luxury Vinyl Tiles**

Primer not necessary over concrete. Drying time 15-20 mins. Walk-over immediately. **Interior use.**

Kit Unit Size: 1.06 gal/unit

Coverage: Approx. 540 sq.ft.

Also available in 2.7 gal/unit

Coverage: Approx. 1,380 sq.ft.



SCHÖNOX EMICLASSIC PH IRRELEVANT UP TO 90% RH

**Universal, No-Latex,
Pressure-Sensitive Acrylic Adhesive
for all Flexible Coverings**

Suitable for bonding all types of vinyls, carpets, linoleum, and synthetic rubber coverings, as well as impact sound insulation underlayments on porous and non-porous substrates in **interior areas**.

Unit Size: 4 gal/unit

Coverage: From 380-850 sq.ft. with varying notched trowel



SCHÖNOX MULTIFIX

PH IRRELEVANT UP TO 75% RH

Acrylic Adhesive and Tackifier

Suitable for releasable bond of carpet tiles and cushioned vinyl on suitable substrates in **interior areas**. Water soluble. No primer needed.

Unit Size: 3 gal/unit

Coverage: Approx. 1500 sq.ft. with roller



SCHÖNOX HPS 1100

Clear Thin Spread Acrylic Adhesive

Suited for bonding of VCT on suitable substrates in **interior areas**. Solvent-free, quick dry time, and extended working time. Ready for immediate foot traffic and heavy traffic after 2 hours. Up to 90% RH/11 pH.

Unit Size: 4 gal/unit

Coverage: 1/16" x 1/16" x 1/16"

125-175 sq.ft. per gal, 1/32" x 1/16" x 1/32" 200-300 sq.ft. per gal



SCHÖNOX HPS 92

Acrylic Adhesive for Resilient Flooring

Suited for bonding of VCT, vinyl enhanced floor tile, solid vinyl floor tile, LVT, and planks on suitable substrates in **interior areas**. Up to 92% RH/11 pH.

Unit Size: 4 gal/unit

Coverage: Approx. 1280 sq.ft. with notched trowel



SCHÖNOX PU 900

PH IRRELEVANT UP TO 85% RH

Two-Part Universal Polyurethane Adhesive

Suitable for bonding of vinyl and rubber floor coverings as well as other materials on suitable substrates in **interior areas**.

May be used as a crack repair compound to fill or seal dormant cracks or joints.

Unit Size:

Part A (resin): 0.86 gal/unit

Part B (hardener): 0.23 gal/unit

Coverage: Approx. 105 sq.ft. with notched trowel



SCHÖNOX PROTECT

PH IRRELEVANT UP TO 95% RH

Solvent-Free Universal Resilient Flooring Adhesive

Suitable for bonding of sheet vinyl, VCT, LVT, sheet synthetic rubber coverings, sheet linoleum coverings, rubber and cork granulated underlayments, and artificial turf in **interior and exterior areas**.

Unit Size: 2.5 gal/unit

Coverage: From 270-550 sq.ft. with varying notched trowel

*Refer to Technical Data Sheets for more information

Toll Free: 855.391.2649 15



WATERPROOFING & CRACK ISOLATION MATERIALS

For installations in residential and commercial wet areas such as kitchens, bathrooms, showers, balconies, terraces, and swimming pools before the installation of ceramic tile.



SCHÖNOX HA

Ready-Mixed, Rollable Waterproofing and Crack Isolation Membrane

For installation under ceramic tiles and stone in residential and commercial wet **interior areas**. Install as a crack-isolation membrane without waterproofing requirements, by applying one coat at the required thickness.

Unit Size: 3.8 gal/unit

Coverage: Approx. 200 sq.ft.



SCHÖNOX iFIX™

DUST-REDUCED


Rollable Waterproof Sealing Adhesive

Unique 2-in-1 time-saving system for bonding Schönox AB in residential and commercial wet areas. Suitable in heavy loaded commercial wet areas.

For interior and exterior use. Acts as a waterproof crack isolation membrane up to width of 3/16".

Unit Size: Powder: 7.7lb., Liquid: 1.61 gal

Coverage: Approx. 105 sq.ft.



SCHÖNOX AB

Sealing, Waterproofing Sheet Membrane

Made of polyethylene and covered with a special fleece. Install using 1 unit of Schönox iFix™ sealing adhesive per 10 m roll for commercial and residential wet areas. Suitable for use under ceramic and natural stones.

Total sq.ft.: 105 sq.ft./roll

Roll Size: 32.8 ft. L, 3.28 ft. W

323 sq.ft./roll also available

WATERPROOFING ACCESSORIES




SCHÖNOX ST Sealing Tape

164 ft. roll




SCHÖNOX IC Interior Corners



SCHÖNOX EA Exterior Corners




SCHÖNOX ST FC Sleeve



SCHÖNOX ST D 8 Pipe Cover

4.73" x 4.73" with
5/16" hole diameter



SCHÖNOX ST D 15 Pipe Cover

4.73" x 4.73" with
5/8" hole diameter

*Refer to Technical Data Sheets for more information

Toll Free: 855.391.2649 17



TOOLS & ACCESSORIES

For comprehensive information on all of our Tools and Accessories go to hpsubfloors.com.

Water Bucket / 2.5 gal.



Barrel / 15 gal.



Mixing Bucket / 5 gal.



Foam Tape 2" x 33'



Reusable KH Fix and Roll and Go™ Tray



RS 50 Foam Tape
2.5" x 65'



Fleece Jacket
Sizes: M, L, XL, XXL



Pants
Sizes: S, M, L, XL, XXL



Coveralls
Sizes: S, M, L, XL, XXL





HPS Schönox endorses
Bosch HEPA VAC Series Dust Extractors

TOOLS & ACCESSORIES

For comprehensive information on all of our
Tools and Accessories go to hpsubfloors.com.

Gunite Shoes



Leveling Trowel



24" Smoothing Trowel



Porcupine Roller with Frame



20" KH Fix Roller with Handle



20" Adhesive Roller with Handle



Maximize your workflow with Schönox self-levelers and Graco ToughTek Series Mixing Pumps.

Contact your Schönox representative for more info.

Graco SL340e
Piston Pump



Graco MP40
Rotor Stator Pump



2 Blade Mixing Paddle



Oval 26" Mixer



Collomix LevMix




Hippo Mixer



Roller Holder



24" Gauge Rake





Take your business to a whole new level.
Call 855.391.2649 or visit hpsubfloors.com to learn
how your projects run smoother with Schönox On It.

| in

| f



| You
Tube



511 Wilhite Street, Florence, AL 35630
Toll Free 855.391.2649 | Fax 256.246.0346
hpsubfloors.com

Download the Schönox app!



HPS North America, Inc. is a TMT America Company

©2020_HPS_SCHÖNOX_20-0889_PRODUCT_GUIDE_REV_08.20_10K